ACCUD

ACCURATE MEASUREMENT



See full product range at: accud.com.au

Coating Thickness Gauge

Series CF/CN1250



Features

F type probe: measure the thickness of non-magnetic coatings (zinc, copper, enamel, plastic and so on) on magnetic subtracts (iron, steel)
N type probe: measure the thickness of non-conductive coatings (varnish ,enamel, plastic and so on) on conductive subtracts (zinc, copper, aluminum)
V-type probe to measure the cylinder easier
Single and continuous working mode
Low and high limits setting with judgement
With average calculation function

Specifications

Part No	Specification
AC-CF1250	Probe type: F Range: 0 ~ 1250□m Accuracy: 2□m(0 ~ 100□m) Accuracy: 2%(100 ~ 1250□m) Resolution: 0.1□m (0 ~ 999□m) Resolution: 1□m (1000 ~ 1250□m) Memory: 500 Power supply: 3xAAAbatteries Dimension(L×W×H): 150×50×29mm Weight: 170g Included accessories Main unit: 1pc Calibration foil: 1set Calibration base: 1pc AAA battery:3pcs
AC-CN1250	Probe type: N Range: 0 ~ 1250□m Accuracy: 2□m(0 ~ 100□m) Accuracy: 2%(100 ~ 1250□m) Resolution: 0.1□m (0 ~ 999□m) Resolution: 1□m (1000 ~ 1250□m) Memory: 500 Power supply: 3xAAAbatteries Dimension(L×W×H): 150×50×29mm Weight: 170g Included accessories Main unit: 1pc Calibration foil: 1set Calibration base: 1pc AAA battery: 3pcs

© 2026 M Gamer Pty Ltd