ACCUD

ACCURATE MEASUREMENT



See full product range at: accud.com.au

Coating Thickness Gauge

Series CFN1500B



Features

Integrated F and N type probe
F type probe is used to measure the thickness of non-magnetic coatings (zinc, copper, enamel, plastic and so on) on magnetic subtracts (iron, steel)
N type probe is used to measure the thickness of non-conductive coatings (varnish ,enamel, plastic and so on) on conductive subtracts (zinc, copper, aluminum)
Large display screen
V-type probe to make the cylinder measurement easier
With um/mil unit conversion
Automatic power on/ off
With back light

Specifications

Part No	Specification
AC-CFN1500B	Range: 0 ~ 1500□m Accuracy: 2□m(0 ~ 100□m) Accuracy: 3%(100 ~ 1500□m) Resolution: 0.1□m (0 ~ 99.9□m) Resolution: 1□m (100 ~ 1500□m) Min. measuring area: 25×25mm Min. curvature: convexity: 5mm; concave: 30mm Min substrate thickness: magnetic material: 0.2mm; non magnetic material: 0.05mm Memory: 30 sets Power supply: AAAbatteries Dimension(L×W×H): 120×52×26mm Weight: 170g Included accessories Main unit: 1pc Calibration foil: 1set Calibration base: 1set AAA battery: 2pcs

© 2026 M Gamer Pty Ltd