

ACCUD

ACCURATE MEASUREMENT



See full product range at: accud.com.au

Coating Thickness Gauge

Series CFN1500B



Features

- Integrated F and N type probe
- F type probe is used to measure the thickness of non-magnetic coatings (zinc, copper, enamel, plastic and so on) on magnetic substrates (iron, steel)
- N type probe is used to measure the thickness of non-conductive coatings (varnish, enamel, plastic and so on) on conductive substrates (zinc, copper, aluminum)
- Large display screen
- V-type probe to make the cylinder measurement easier
- With um/mil unit conversion
- Automatic power on/ off
- With back light

Specifications

Part No	Specification
AC-CFN1500B	<div>Range: 0 ~ 1500µm</div> <div>Accuracy: 2µm(0 ~ 100µm)</div> <div>Accuracy: 3%(100 ~ 1500µm)</div> <div>Resolution: 0.1µm (0 ~ 99.9µm)</div> <div>Resolution: 1µm (100 ~ 1500µm)</div> <div>Min. measuring area: 25×25mm</div> <div>Min. curvature: convexity: 5mm; concave: 30mm</div> <div>Min substrate thickness: magnetic material: 0.2mm; non magnetic material: 0.05mm</div> <div>Memory: 30 sets</div> <div>Power supply: AAAbatteries</div> <div>Dimension(L×W×H): 120×52×26mm</div> <div>Weight: 170g</div> <div>Included accessories</div> <div>Main unit: 1pc</div> <div>Calibration foil: 1set</div> <div>Calibration base: 1set</div> <div>AAA battery: 2pcs</div>