

ACCUD

ACCURATE MEASUREMENT



See full product range at: accud.com.au

Coating Thickness Gauge

Series CFN1500B



Features

Integrated F and N type probe
F type probe is used to measure the thickness of non-magnetic coatings (zinc, copper, enamel, plastic and so on) on magnetic substrates (iron, steel)
N type probe is used to measure the thickness of non-conductive coatings (varnish, enamel, plastic and so on) on conductive substrates (zinc, copper, aluminum)
Large display screen
V-type probe to make the cylinder measurement easier
With um/mil unit conversion
Automatic power on/ off
With back light

Specifications

Part No	Specification
AC-CFN1500B	<p>Range: 0 ~ 1500μm Accuracy: 2μm (0 ~ 100μm) Accuracy: 3% (100 ~ 1500μm) Resolution: 0.1μm (0 ~ 99.9μm) Resolution: 1μm (100 ~ 1500μm) Min. measuring area: 25x25mm Min. curvature: convexity: 5mm; concave: 30mm Min substrate thickness: magnetic material: 0.2mm; non magnetic material: 0.05mm Memory: 30 sets Power supply: AAA batteries Dimension (LxWxH): 120x52x26mm Weight: 170g</p> <p>Included accessories Main unit: 1pc Calibration foil: 1set Calibration base: 1set AAA battery: 2pcs</p>