

Precision Height Gauge

Series HG50/100





Features

High accuracy Response speed: max. 500mm/sec Working table is made of ceramic With spindle lift knob Optional accessories series 270

Specifications

| Part No | Specification |
|----------|---|
| AC-HG100 | Measuring range: 0-100mm Accuracy: 3µm* Resolution: 0.1µm/1µm Repeatibility: 0.5µm Tip force: 1-1.5N Dimension of working table: 110x110mm Flatness of working table: 1µm Power supply: 100-240V adapter Working temperature: 0°C - 40°C Weight: 4kg INCLUDED ACCESSORIES Main unit: 1pc Working table: 1pc Needle contact point: 3pcs Flat contact point: 2pcs AD/DC adapter: 1pc Spindle lift knob: 1pc |
| AC-HG50 | Measuring range: 0-50mm Accuracy: 1.5µm* Resolution: 0.1µm/1µm Repeatibility: 0.5µm Tip force: 1-1.5N Dimension of working table: 110x110mm Flatness of working table: 1µm Power supply: 100-240V adapter Working temperature: 0°C - 40°C Weight: 4kg INCLUDED ACCESSORIES Main unit: 1pc Working table: 1pc Needle contact point: 3pcs Flat contact point: 2pcs AD/DC adapter: 1pc Spindle lift knob: 1pc |

